

GL-11 Injector Automatic Lubrication System

Available Electronically Only



High volume output at high pressures for the most demanding applications

- Combine with GL-1s and GL-32s in the same Single Line Parallel System to provide a full range of outputs
- Outperforms the competition-tested to over 250,000 cycles without failure!
- Bolt-on compatible with Lincoln® Centro-Matic SL-11® injectors





System Setup Tips

- Run branches off main line and "Tee Out" to banks of injectors instead of in-series
- Locate injectors as close to bearings as possible to minimize line length to bearing to enable max pressure to reach injectors
- · Place pressure switch beyond last injector
- Use large diameter tubing (1/4 in.) for bearing feed lines
- Make sure you have enough pressure to achieve normal 2,500 psi (172 bar)
- Make sure you vent down to the minimum reset pressure of your smallest injector

To adjust:

- 1. Loosen the lock nut
- 2. Rotate 5/8 inch output adjustment nut clockwise to decrease grease output– decrease the travel of the piston
- 3. Rotate 5/8 inch output adjustment nut counter-clockwise to increase grease output-increase the travel piston



Precision-honed Components for Reliable Operation in the Harshest Environments

Easy Hex Nut Volume Adjustment

Visual Indicator Pin

Lock Nut

Technical Specifications

reennieur opeenieurions		
Maximum Operating Pressure	3,500 psi (241 bar)	
Minimum Operating Pressure	1,000 psi (69 bar)	3
Suggested Operating Pressure	2,500 psi (172 bar)	19
Reset Pressure	600 psi (41 bar)	
Output Range*	0.05 - 0.50 in ³ (0.82 - 8.2 cm ³)	
Recommended Fluids	Grease NLGI grade #1 or higher	
Instruction Manual	313704	
Design Guide	309015	
Zerk Fitting Outlet	1/8 in NPSF	10
Supply Line Outlet	1/4 in NPSF	G
Inlet	1/2 in npt	1.12

*Limited by operating temperatures and lubricant additives

How many injectors in this picture?



Ordering Information

24A918	GL-11 Injector
114916	GL-1 & GL-11 Zerk Fitting and Cap Kit
24B359	GL-11 Overhaul Kit

Contact us today!

To receive product information or talk with a Graco representative, call **800-533-9655** or visit us online at **www.graco.com**.

©2009 Graco Inc. Form No. 340446 Rev. A 7/09 All other brand names or marks are used for identification purposes and are trademarks of their respective owners. All written and visual data contained in this document are based on the latest product information available at the time of publication. Graco reserves the right to make changes at any time without notice.